



52LH1WP



- Fully approved IP66 weatherresistant, protected against powerful water jets and against short-term flooding
- Screen dimension: 132 cm (52 inch)
- Winter mode: Guaranteed monitor usability at temperatures ranging from $-20\text{ }^{\circ}\text{C}$ to $+45\text{ }^{\circ}\text{C}$
- Vandalism- and tamper-proof anti-reflective glass
- Anti-corrosive anodized aluminium cabinet
- Impressive picture quality: Full HD
- Ideally suited for various indoor and outdoor installations as well as 24/7 applications
- Extensive input & output terminals
- Network integration (optional) for maintaining and controlling the monitor on the LAN

52LH1WP

Model	52LH1WP
EAN Code	4994334248084
Category	Professional LCD monitor
Type	Liquid crystal display panel
IP Rating	IP66*
Screen size (diagonal image)	52" (132 cm)
Active screen area (W x H)	115.2 x 64.8 cm
Aspect ratio	16 : 9
Resolution in pixels	1,920 x 1,080 (HDTV 1,080p)
Pixel pitch	0.2 x 0.6 mm
Brightness	500 cd/m ²
Contrast ratio	1,500 : 1
Viewing angle	176° (horizontal and vertical)
Response time	6.5 ms (gray to gray)
Grey scale value	8 bit
Number of colours	16.7 Mio
Colour Systems	PAL, NTSC3.58 (AV in), SECAM
Computer compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA
Input terminals	D-Sub15 5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) Scart (RGB) Video RS232 (D-Sub 9 pin) 2 x RCA (R/L mono) for Audio DVI-D (digital/HDCP) 3.5 mm Stereo Jack for Audio
Output terminals	5 x BNC (RGBHV, Y-Pb/Cb-Pr/Cr) Component (Y, Pb, Pr) BNC (Video) RS232 (D-Sub 9 pin) 2 x RCA (R/L mono) for Audio External speaker output (2 x 10 W)
Operating temperature	-20 °C to +45 °C (winter mode)
Storage Temperature	-20 °C to +60 °C
Voltage	100-240 V (50/60 Hz)
Power consumption	290 W/2 W (stand-by mode)
Dimensions (W x H x D)	1,304 x 800 x 234.5 mm
Weight	74 kg
Vesa mounting sizes	420 x 516 mm, 997 x 420 mm
Colour of cabinet	Silver
Warranty	3 years
Standard accessories	User manual, remote control, batteries, power cable
Optional accessories	PJ Net Organizer Plus (POA-LN02)
Special features	Fully sealed aluminium case, weatherproof, reinforced, anti-reflection glass screen surface, 24h/7 approved, vandalism-proof anti-reflective glass, extensive input & output terminals, protection against penetration of dust, winter mode, portrait mode

* IP = Protection class



Technical specifications subject to change without notice. Date 04/2008

